




- Rugged construction
- Quick fit clip installation
- Moulded coaxial cable


The performance and range of portable equipment can often be considerably improved by better positioning of the antenna. Spring clip antennas provide an easy way to do this, providing elevation and clearance from surrounding objects. The combination of better positioning with the performance of an end fed 1/2 wave antenna makes the CD range ideal for temporary and semi permanent applications.

The jaws of the spring clip are moulded in nylon and are fully adjustable for any angle. The antenna is protected from the elements by a weather protective moulding around the coaxial feeder cable.


Typical H-Plane (390MHz)




Typical E-Plane (390MHz)



Typical VSWR*



*Measured in free space with 3m (9.8') CS23 cable



Part No.

CD390

Electrical Data

Frequency Range (MHz)	380-410
Operational Band	S1
Peak Gain: Isotropic	3dBi
Compared to ¼ wave	1dB
Typical VSWR	<2.2:1
Polarisation	Vertical
Pattern	Omni-directional
Impedance	50Ω
Max Input Power (W)	5

Mechanical Data

Total whip length (mm)	420 (1.4')
Operating Temp (°C)	-40° / +80°C (-40° / 176°F)
Colour	Black

Cable Data

Type	CS23
Length (m)	3 (9.8')
Diameter (mm)	5 (0.2")



Panorama Antennas Ltd
Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444
F: +44 (0)20 8877 4477
E: sales@panorama-antennas.com
www.panorama-antennas.com

Waiver: The data given above is indicative of the performance of the product/s under particular conditions and does not imply a guarantee of performance. These specifications are subject to change without notice.

Copyright © Panorama Antennas Ltd. All rights reserved.